



**SUPER DIESEL ENGINE OIL  
SAE 10W 40, 15W40, 20W 50**

**DESCRIPTION:** High Performance engine oil designed for a wide range of Diesel and Petrol applications with or without Turbo and Supercharged applications, requiring API SG/CF-4, SJ/ CH-4, and SL/CI-4 Performance lubricants.

**BENEFITS:** Increase power output and minimizes fuel economy  
Improves consumption  
Lowest maintenance cost.  
Prolonged oil life.

**PERFORMANCE STANDARDS:** MB 229.1, 228.1, 228.3, 228.5. BMW Approval  
Volvo VDS-2, MAN 271/M 3275, ALLISON C-4, MACK EOM PLUS, Volkswagen  
500.00, 501.00, 505,1, 505.00 Approval  
Cummins CES 20078 Approval

- MEETS OR EXCEEDS:**
- MIL-L-2104F
  - CCMC D4
  - ADE SHEET 3 & 4
  - SAE 30 & 15W40 ALLOSON C-3 & C-4
  - CAT TO-2
  - KOMATSU MICROCLUTCH TEST
  - MACK EO-K/2

**TYPICAL PHYSICAL CHARACTERISTICS**

Grade	10W 40	15W 40	20W 50
Viscosity cSt@ 40 °C	95.8	115	135
Viscosity cSt 100 °C	14.5	15.4	19
Viscosity Index	157	135	150
TBN mg KOH/gm	11	11	11

**PERFORMANCE LEVEL:** API CF-4/SG, CH-4/SJ, CI-4/SL

**PACKAGING:** 500 ml, 5 liter, 20 liter, 210 liter, 1000 liter

