



HYDRAULIC OILS
ISO TYPE HM TYPE HL AND HLP
32 / 46 / 68 / 100 / 150

DESCRIPTION: Hydraulic oil is a high quality anti-wear hydraulic fluid, designed for the use in mobile and stationary pressure hydraulic systems.

PERFORMANCE EXCEEDS REQUIREMENTS OF:

Abex Denison HF-i, HF-2, HF-0
 Cincinnati Milacron P-68, P-69, P-70. DINi
 DIN 51524 part2
 Ford M-GC32
 GM LH -04-1, LH-06-01, LH-15-1
 BF Goodrich 0152, Lee Norse 100-1
 US Steel/Vickers M-2950-s, I-286-s

TYPICAL PHYSICAL CHARACTERISTICS:

ISOVG.	32	46	68	100	150
Flash point	200	210	215	220	230
Pour Point	-33	-33	30	-21	15
Viscosity cSt @ 40 °C	30	44	66	95	143
Viscosity cSt 100 °C	5.4	6.7	8.6	10.8	14.3
Viscosity Index	109	106	104	97	97
FZG Stage Passed (min)	10	10	10	10	10
Zinck ppm	440	440	440	440	440

PACKAGING: 5 liter, 20 liter, 210 liter, 1000 liter

